Format No.: QAD-CR/13/F (Rev.03)

Declaration of Performance - No: JSHL-UKCA-HR EN1.4307

Construction Products (Amendment etc.) (EU Exit) Regulations 2020, UK Statutory Instrument 2020 No. 1359

| or the construction product | | Stainless steel hot rolled annealed pickled coil/sheet/plate | |
|-----------------------------|---|---|--|
| 1. | Unique identification code of the product type: | Grade 1.4307,1D,P, EN 10088-4:2009 | |
| 2. | Intended use: | Flat section for steel construction | |
| 3. | Manufacturer: | Jindal Stainless Limited, Hisar Hot & Cold Rolling Division, O.P. Jindal Marg, Hisar, Haryana- 125005 (India) | |
| 4. | Authorized representative: | None | |
| 5. | System of AVCP: | System 2+ | |
| 6. | Harmonised standard: | EN 10088-4:2009 | |
| | Approved body: | LRQA Verification Ltd Approved body No. 0038 | |
| 7. | Declared performance: | | |

| Essential characteristics | Performance | Harmonised technical specification | |
|--|---|------------------------------------|--|
| Dimensions and shape | EN ISO 18286/ EN ISO 9444-2 | | |
| Tensile Strength (MPa) | 500-700 | | |
| Yield Strength (MPa) | 200 Min | | |
| Elongation (%) | 45 Min | | |
| Impact Strength (Joules) (Transverse) | 60 Min | | |
| Weldability | Chemistry confirms to Table 3 | EN 10088-4:2009 | |
| Durability | Chemistry confirms to Tabe 3 & Resistance to Intergranular corrosion. | LIV 13000-4.2003 | |
| Fracture toughness (Joules) (Transverse) | 60 Min | | |
| Cold formability (% Elongation) | 45 Min | | |

The performance of the product identified above is in conformity with the set of declared performance. This Declaration of Performance is issued, in accordance with Construction Products (Amendment etc.) (EU Exit) Regulations 2020, UK Statutory Instrument 2020 No. 1359, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

(Name and Function): Mr. B.R.Chowdhury, Head of Department, Quality Assurance

B.R.Chowdhury

(Place, Date, Signature): Hisar, 06.03.2023